

## High speed ADC: one that no one had ever told you

Gianfranco, I2VGO

The performance of a band HF receiver, direct RF samples are decided by two or three maker ADC high speed, in the world.

But only Linear Technology produces ADC with bits effective bits, ENOB, of constant value versus frequency. It is what allows for the same values of MDS (at equal bandwidth) from 1.8 to 30 MHz or 50 MHz) with ideal local oscillator.

The best design is the one that has the smallest possible **Delta**.

Where Delta is = SNR real receiver - SNR ADC (without pre-amplifier in front ADC)

### **Absolute limits of NF and Clip level of the best ADC for Receiver Full DSP with max frequency 50 Mhz.**

Under these conditions:

- a) Oscillator Phase noise = infinite dBc and white noise from 100 -200 kHz (corner frequency) to 120 MHz= -174 dBm/Hz (NF =0 dB). In this conditions rms Jitter = 0 fS
- b) Delta = 0 dB

	LTC 2208- 14BIT	LTC 2208- 16 BIT
Sample's frequency	120 MHz	120 MHz
Nyquist's frequency	60 MHz	60 MHz
Noise Power in Nyquist band.	-77. 8 dBm	- 77. 8 dBm
Minimum SINAD S/(N+D)@30 MHz	75.1 dB	75.9 dB
Effective Number of Bits, ENOB	12. 1	12. 3
Sensitivity and Bit loss	11. 4 dB      1.9 bit	22.2 dB      3.7 bit
Clip Level = Max input signal power with driver voltage gain = 0 dB. Unbal. 50 ohm input and out balanced 800 ohm.	10. 4dBm	10.4 dBm
Noise Figure, NF	31. 5 dB	30.7 dB
MDS@500 Hz CW	-115.5 dBm	-116. 1 dBm
MDS@2400Hz SSB	-110.7 dBm	-111. 3 dBm
Acquisition delay time jitter	70 fS	70 fS
Price from >100 pieces	77. 65 \$	91. 65 \$

I2VGO

You can view that a move from 14-bit to 16-bit physically the gain is **only 0.8 dB with an ideal OL and an ideal project.**

In practice with real oscillator and Delta designer a receiver with 14 bit ADC can be better than an RX with 16-bit ADC.


Today we reached 12.8 ENOB. Acquisition time delay Jitter = 45 fS with \$ 180: LTC2107

I calculated the SNR real of ADC the best in the world with the following data:

- 1) Acquisition time delay Jitter = 45 fS
  - 2) Average differential nonlinearity, DNL = + - 0.5 bits
  - 3) Effective input noise generated by the ADC 1.9
- Input frequency = 30 MHz.  
N: Number bit physically

By setting 1) = 0 , 2)= 0 and 3) = 0, you get the SNR ideal  
From SNR ideal and SNR real it obtained the ENOB real and ideal and they were represented in the graph.

This is the comparison of ENOB ideal with ENOB real.  
You will understand why there are no ADC to 18 bits High speed.  
The case is a small capacitor into block: Sample& Hold



<b>COMPARING THE TWO ADC USED, ON ASSUMPTIONS THAT IC 7300 USING LTC 2208 -14 (NOT OFFICIAL SOURCE).</b>		
Specification	<b>Perseus LTC 2206 14 bit</b>	<b>IC 7300 -LTC 2208 14 bit-?</b>
Sample's frequency	80 MHz	120 MHz
Nyquist's frequency	40 MHz	60 MHz
Noise Power in bandwith Nyquist	-77.8dBm	-76 dBm
Minimum SINAD S/(N+D)	75.7 dB- at 15 MHz	75.1 dB-at 30 MHz
Effective Number of Bits, ENOB	12.3	12.2
Acquisition delay time jitter	80 fs	70 fs
<b>COMPARISON ONLY NF AND CLIP LEVEL OF RX OF PERSEUS (MEASURED BY I2VGO- 2008 ) AND IC7300 ( MEUSURED BY NC0B. 4/10/2016 EMAIL TO I2VGO) AT 14.2 MHZ.</b>		
Pre off and bench filter preselector		
Noise Figure	20 dB.	25 dB
BDR @10kHz	117 dB,	101 dB
Clip level	-3.5 dBm	-9 dBm
Pre 1 On		
Noise Figure	19 dB	<b>6dB</b>
BDR @10kHz	?	?
Clip Level	-7 dBm	-22 dBm
Pre 2 On		
Noise Figure	-----	5 dB
BDR @10kHz		?
Clip Level		-26 dB
Pre off with IP+Off		
Noise Figure	-----	14 dB
BDR @10kHz		81 dB
Clip Level		-9 dBm
year supply	September 2007	April 2016

Reference

Analog-Digital Conversion, Walt Kester; Analog Devices Inc ISBN 0-916550-27-3 (2004)

Gianfranco, I2VGO  
SWL i1-12559 ex I1VGO  
ARI Honorary member

Vimercate 04/18/2016